



OKAMI
CCTV

OKAMI ENTERPRISES CO.,LTD.
[HTTP://191CCTV.COM](http://191CCTV.COM)



กล้องวงจรปิดรุ่น OK-IP420TC-F

Resolution:1920(H)×1080(V),output Real-time HD 1080P image

***1/2.9" SONY Low Illumination CMOS Sensor**

***Support Digital WDR,3D-DNR**

***Dual IR-Cut filter;4pcs IR LED 60M IR Distance.**

***H.264/MJEG is optional, dual streaming, low bandwidth,high quality.**

***Support motion detection, network fault detection and alarm video, image snapping**

***Support ONVIF protocol.**

***Free PC and Smartphone application.**



OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.
[HTTP://191CCTV.COM](http://191CCTV.COM)



กล้องวงจรปิดรุ่น OK-IP420TC-F

Model		OK-IP420TC-F	
Chipset	IMX323 + Hi3516C		
Sensor	IMX323		
Effective Pixels	1920(H)×1080(V)		
Min.Illumination	Color mode 0.05Lux @F1.4; B/W:0Lux(IR ON)		
S/N	≥50db(AGC OFF)		
WDR	≥100db		
Day&night / IR Parameters	4pc 42μ IR led 60M IR Distance		
Lens	2.7-12mm Manual Zoom Lens, 3MP HD Lens		
Network Interface	10/100M BASE-TX,RJ-45 connector		
Video Compression	H.264 Baseline Main Profile; MJPEG/JPEG		
Resolution	Master Streaming	1920*1080, 1-25(30) FPS 1280*720, 1-25(30) FPS	
	Second Streaming	720*576, 1-25(30)fps/sec	640*480, 1-25(30)fps/sec
		640*352, 1-25(30)fps/sec	320*240, 1-25(30)fps/sec
Recording	Recording set up to record by motion trigger, alarm trigger, manual, or schedule		
Alarm Output	FTP,E-mail, Explorer, Software		
Network protocol	TCP/IP,UDP,RTP,RTSP,RTCP,HTTP,DNS,DDNS ,DHCP,FTP,NTP,PPPOE,SMTP,UPNP		
ONVIF protocol	Support		
Remote	Computer	IE 6.0 or up	



OKAMI
CCTV

OKAMI ENTERPRISES CO.,LTD.
[HTTP://191CCTV.COM](http://191CCTV.COM)



กล้องวงจรปิดรุ่น OK-IP420TC-F

View	Mobile Phone	iPhone, Android
Operating Temperature / Operating Humidity		-20°C - +55°C / 0% - 90%
Power Supply		DC12V / 2W(MAX)
Operating Temperature		-10°C to +50°C, RH 80% Max
Water resistance		IP66
Storage temperature		-20°C to +60°C, RH 90% Max
Dimension		287mm(L)*150mm(W)*150(H)mm
Weight		950g